

KOENIG & BAUER


Print&Apply 4PL tamp

PACKAGING		
Entry	Advanced	High-End

Labeller with tamp applicator

Labels straight surfaces at standstill or on the fly

label width 4" or 6"



we're on it.

KOENIG & BAUER

Content

Labeling	1
Recommended use for label materials	1
Application examples	2
4PL tamp	2
Connectivity	4
Automation	5
Quality	6
Contact	6

KOENIG & BAUER

Labeling

The quality of industrial marking with labels depends on the **selection** of the **label material** and its processing.

Recommended use for label materials

Quality	Temperature	Durability	Range of applications	Addendum
Paper standard thermal	-20 to +80°C	Conditionally	Simple marking	Cost-effective; for short-term marking
PE/PP	-20 to +80°C	Good: with moisture, chemicals, cleaning agents	full range	Good resistance; Very good print image; Good price/performance ratio
PVC	-20 to +90°C	Good: with moisture, chemicals, cleaning agents, weather conditions	full range	Suitable for outdoor applications; UV-resistant
PET	-40 to +150°C	Good: with humidity, chemicals, cleaning agents, high temperatures	full range, Automotive	Very high mechanical strength and hardness for demanding, permanent marking
Polyamid	-4 to +300°C	Good: with humidity, chemicals, cleaning agents, high temperatures	full range	Good dimensional stability
Laser Combustion Colour change	+260°C <small>of short duration</small> +150°C	Very good: with humidity, chemicals, cleaning agents, high temperatures	full range	Very high resistance for demanding marking Emission-free labeling (color change) Rewritable
Special materials/ functional labels		Depending on application	e.g. paint or surface protection, sealings	Process support and -optimization

Application examples

4PL tamp





KOENIG & BAUER

4PL tamp

Model

4PL tamp

Printer	Zebra ZE511 4“	Zebra ZE512 6”
Print resolution	300dpi	
Ribbon length	600m	
Label roll max. Diameter	300mm, 400mm (option)	
Measurements (L x W x H)	890 x 480 x 440 mm	
Weight	40 kg	
Enclosure class	IP 20	
Connected loads	115 V / 230 V ; 50 Hz / 60 Hz ; 110 VA	
<div></div>		
Environment	Temperature + 5° bis + 40° C, relative humidity 20 - 95 %	
Operation	PC-Software, Touchscreen Terminal	
Interfaces	Ethernet TCP/IP, RS 232, I/O, USB	
Controller	Siemens Logo!8	
Accessories	Protection cover, Mounting brakets, Stand, Sensor, Scanner, Camera, Touch-Panel, Beacon, Caster rollers	

KOENIG & BAUER

Connectivity

Packstation Sandwiches


Select the product:

ProdCode:Pro...

ProdCode	ProdName
SDW01	Three Cheese Medley
SDW02	Tomato Brie Basil Sandwich
SDW03	Chicken Croissant Sandwich
SDW05	Tuna Sandwich
SDW06	Three Cheese with Vegetables
SDW07	Vegi Sandwich
SDW08	Hamburger
SDW09	Chili Cheese Dog
SDW10	Chicken & Bacon Melt
SDW11	Chicken Bacon Pita Sandwich

Chicken Croissant Sandwich

Crispy croissant with rotisserie chicken with mayonnaise and basil pesto



€3,00

Net weight: 180 g Best before: 14.6.2020

Nutrition Information	
	Per 100 g %Reference intake (RI)
Energy	2467 kJ / 590 kcal 30% RI
Fat	22 g 40% RI
Of which saturates	5 g 10% RI
Carbohydrate	50 g 16% RI
Of which sugar	4 g 8% RI
Protein	39.4 g 79% RI
Salt	1.4 g 28% RI
Vitamin C	1.5 mg 3% RI

Salt content is exclusively due to the presence of naturally occurring sodium.

* Reference intake of an average adult (8400 kJ / 2000 kcal)


INGREDIENTS: Flour, water, chicken, basil pesto, mayonnaise

Select the printer:

ZEBRA ZE500-6 LH-300dpi ZPL

Number of copies:

1

 **Print**

Manage data

Application Configuration

User interfaces and automation tailored to the specific application and according to customer specifications.

Scanner

For finding barcodes, e.g. to automatically overlay an existing label. With the scanner the barcode on the label can pass final control.


Camera systems

For analysing the object and automatically determining the label position. Finally, the camera can be used to perform a comprehensive inspection of the label, contents and position.

Sensors and switches

For sensorical location of the label position and for proximity determination of e.g. sensitive objects.

Automation



Our team from Koenig & Bauer Coding GmbH offers you an experienced and technically skilled team with experience in connectivity and automation.

We are able to act as a binding provider of automated overall solutions.

We assure you technical support before and after the order including a risk analysis. We visualize and simulate the project. We are using standard components to make our solutions transparent and flexible. The applications are produced order-related and commissioned by employees with direct relation to the project.

Quality

ISO certification according to DIN EN ISO 9001-2015

Made in Europe.

Our quality standards include the process of continuous improvement. Design and technical changes are therefore subject to change without prior notice.

KOENIG & BAUER

Contact

Koenig & Bauer Coding GmbH

Benzstraße 11

97209 Veitshöchheim

Telephone: +49 (931) 9085 - 0

Telefax: +49 (931) 9085 - 100

E-Mail: [info-coding\(at\)koenig-bauer.com](mailto:info-coding(at)koenig-bauer.com)